CASTING PAPERS
For Synthetic Leather All Designs of Emboss Type
R series

Jan. 08. 2026

LINTEC Technical Information

1. Product : **R series**

2. Emboss No. : **R-275**

3. Specification :

Grade	Basis Weight (g/㎡)	Thickness (μm)	Glossiness (%)
LXD	160 ± 15	190 ± 20	45 ± 7
PXDH*	-	-	-

This data is intended only as a source of information and is given without any guarantee and does not constitute a warranty.

＊ ：Performance data not available

Grade	Release Type	Application	Recommended Temperature
EV130TPD	Polyolefin	PU	110－130°C
LXD			110－130°C
PXDH / PXDL		PU, Semi-PU, PVC	110－210°C
VX	Special Resin	PVC	190－210°C
ENPLUS		PU, Semi-PU, PVC	110－210°C

-Notes

The statements in this technical information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without any guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications, customers should independently determine the suitability of this material for their specific purpose, Prior to use.

LINTEC Corporation *Linking your dreams*
● **HEAD OFFICE** 23－23, Honcho, Itabashi-ku, Tokyo 173-0001,Japan

Inquiry : Bunkyo Garden Gate Tower 8F
1-1-1 Koishikawa,Bunkyo-ku,Tokyo 112-0002,Japan
Phone:+81-3-3868-7721 Fax:+81-3-3868-7728
www.castingpapers.com