CASTING PAPERS
For Synthetic Leather All Designs of Emboss Type
R series

Jan. 08. 2026

# LINTEC Technical Information

**1. Product** : **R series**

**2. Emboss No.** : **R-55GIM**

**3. Specification** :

| Grade | Basis Weight (g/㎡) | Thickness (μm) | Glossiness (%) |
|---|---|---|---|
| **LXD** | 180 ± 20 | 250 ± 20 | 43 ± 3 |
| **PXDH** | 180 ± 20 | 270 ± 20 | 43 ± 3 |

This data is intended only as a source of information and is given without any guarantee and does not constitute a warranty.

| Grade | Release Type | Application | Recommended Temperature |
|---|---|---|---|
| **EV130TPD** | Polyolefin | PU | 110－130°C |
| **LXD** | | | 110－130°C |
| **PXDH / PXDL** | | PU, Semi-PU, PVC | 110－210°C |
| **VX** | Special Resin | PVC | 190－210°C |
| **ENPLUS** | | PU, Semi-PU, PVC | 110－210°C |

-Notes

The statements in this technical information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without any guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications, customers should independently determine the suitability of this material for their specific purpose, Prior to use.

LINTEC Corporation *Linking your dreams*
● **HEAD OFFICE** 23－23, Honcho, Itabashi-ku, Tokyo 173-0001,Japan

**Inquiry :** Bunkyo Garden Gate Tower 8F
1-1-1 Koishikawa,Bunkyo-ku,Tokyo 112-0002,Japan
Phone:+81-3-3868-7721 Fax:+81-3-3868-7728
www.castingpapers.com